

PoolCop XM8

EXTEND YOUR POOLCOP FOR A FULLY AUTOMATED POOL, AND MORE

Based on the belief that one remote control is enough for any pool, all pool equipment and features should be controlled via one device and interface.

For complete pool management, PoolCop XM8, with its eight additional auxiliary connections, instantly increases the number of relays and inputs, allowing PoolCop to manage a whole range of ancillary equipment.

Everything from pool cleaners to swim jets, fountains to irrigation systems, or simply heating and lighting, can be monitored and controlled directly via a PoolCop, with the addition of the XM8.

It is automatically detected, needing no complicated configuration, and relays the information of all additional features to the PoolCop interface.



PRODUCT ADVANTAGES

- 8 control relays
- 8 input channels
- Simple installation
- Automatically detected by PoolCop
- Direct communication with the PoolCop interface

| RELAY FEATURES | | INPUT FEATURES | |
|-----------------|-------------------|------------------------|------------------------|
| Pool Light | Fountain | Anti-freeze Detection | Electrolysis Diagnosis |
| Pool Cleaner | Borehole | Disinfection Low Level | Pool Cover Detection |
| Pool Heating | Poolhouse | pH Low Level | External Pump Start |
| Disinfection | Garden Irrigation | Flow Switch | External Pump Stop |
| Rinse Valve | Waste Valve | Flooding Detection | Jet Stream Push Button |
| Residual Dosing | Pool Cover Motor | | |
| Transfer Pump | Jetstream | | |
| UV | External Warning | | |
| Spa | | | |



TECHNICAL SPECIFICATIONS

| | |
|---|--|
| REFERENCE | AC6800-D |
| RELAYS (DRY CONTACT) | 8 |
| INPUTS (POTENTIAL FREE) | 8 |
| PACK CONTENTS | XM8 Module with cable |
| DIMENSIONS | 140 x 170 x 95 mm - 0.8 Kg |
| GUARANTEE | 24 months |
| CONTROL AND DISPLAY | Via PoolCop, web interfaces and PoolCop Cloud |
| POOLCOP FIRMWARE, MINIMUM REQUIRED | V33.0 |
| COMMUNICATION WITH POOLCOP | Integrated I2C |
| POWER SUPPLY FROM POOLCOP | 12VDC 300mA |
| PROTECTION | IP55 |
| RELAY MAXIMUM VOLTAGE AND CURRENT | 0-230VAC 6A |
| OPERATING TEMPERATURE | -3 to +45°C |
| COMPLIANCE, ACCREDITATION, CERTIFICATION | CE, UKCA, WEEE |
| INSTALLATION COMPATIBILITY | PoolCop Evolution, PoolCop Genesis, PoolCop Genesis Panel New construction, renovation, or upgrade Residential and commercial pools and spas |
| COMPATIBLE RELAY FEATURES | <ul style="list-style-type: none"> • Pool light • Pool cleaner • Pool heating • Disinfection • Rinse valve • Remnant • Transfer pump • UV • Spa |
| COMPATIBLE INPUT FEATURES | <ul style="list-style-type: none"> • Antifreeze detection • Disinfection - low level • pH - low level • Pool cover • Jetstream push button • Electrolysis diagnosis |
| COMBINED FEATURES (using relay/s and input/s) | <ul style="list-style-type: none"> • JetStream • Pool cover (subject to local legislation) |

